

LT740ME

High Pressure Grease Control Valve

DESCRIPTION

Control Valve for Grease(1/4"NPT(f)) w/ HP Coupler
LT5845ME; For use with all Air Operated High Pressure
Grease Pumps; Grease Inlet: 1/4" NPTF; Operating
Pressure 7500PSI;
6"(15.24CM) Solid Flexed Extension Tube with 1/8"NPT (m)
Thread

Includes High Pressure 7500 PSI Zerk Coupler
Grease Inlet 1/4" NPT (f)

Repair Kit: R82157ME


For Use with all Air Operated High Pressure Grease Pumps
Can be used with PSI Approved Spring Loaded Grease
Hose Attachment

Complete Repair Kits and Parts Available

Other Information: Weight and Dimensions:

BOX Weight: 2LB(.92KG)

BOX Dimensions: Length: 9.0"(22.9cm) X Width:3-
1/2"(8.9cm) X Height: 1-1/2"(3.8cm)



WILLMAR INTERNATIONAL LLC / LUBE TECHNOLOGY

P.O. BOX 456; ADA, MI. 49301 USA

TEL: 616-676-1792; FAX: 616-676-1287

Contact: wilmarllc@gmail.com

Website: <http://www.iserv.net/~wmograde/lube.html>



"Doing Business with the World"

WILLMARLUBE

P.O. BOX 456; ADA, MI. 49301 USA

TEL: 616-676-1792; FAX: 616-676-1287

Contact: sales@willmarlube.com

Website: <http://www.willmarlube.com>